



the natural choice



Location:	La Baña – Northwest of Spain		
Product:	Roofing & Cladding slates		
Color:	True un-fading black		
Characteristics:	Pyrite free, perfect match for Hampton Black slate. Deep dark slate, well recognised for its vertical lines. Very Uniform.		
Format:	Metrics & Imperials. From 30x20 (12"x08") up to 60x30 (24"x12")		
Thickness and Weight:	5mm (1/5")	33 kgs/m2	655 Lbs/square
	6-7mm (1/4")	46 kgs/m2	875 Lbs/square
	9-10mm(3/8")	66 kgs/m2	1275 Lbs/square
	12-13mm(1/2")	80 kgs/m2	1615 Lbs/square

Slate can be supplied either holed or unholed depending upon the roofing system chosen. For more information, check our architects slate guide in www.benatural.es



HEBRA is produced from one source of origin and has a long history of exporting high quality slates to the most demanding markets.

HEBRA is exclusive to **be natural**®. The presence of **be natural**® staff in the quarry guarantees a complete inspection of your order before the collection of your slates.

We control color, thickness, size and selection.

As an additional service, **be natural**® transport your order from the quarry up to your doorstep, wherever you are in the world.

Find out more. Contact us: info@benatural.es
+34 647 763 587
Galicia - Spain

HEBRA have passed all the European and American quality tests and is certified by international approved laboratories as an S1 rated Roofing Slate.



Dimension and Dimensional Variation:	Complies
Nominal Thickness and Variation:	Complies
Mechanical Resistance (MoR):	50.4Mpa / 58.0MPa
Transversal / Longitudinal:	
Failure load:	978.7N / 1023.1N
Transversal / Longitudinal:	
Water Absorption:	Complies
	<0.38%
Carbonate Content:	Complies <0.4%
Thermal Cycling:	T1
Exposure SO2:	S1
Non-Carbonate Carbono Content:	Complies <0.3%
External fire performance:	Deemed to satisfy
Reaction to fire:	Deemed to satisfy class A1
Release of dangerous substances:	None in specified conditions of use



www.hebraslate.com

